



NOTE:
 1.MATERIAL:
 1.1 INSULATOR:LCP E130I UL94V-0;BLACK
 1.2 CONTACT:C2680-H(T=0.20mm)
 1.3 PEG:C2680-H(T=0.20mm)
 2.ELECTRICAL CHARACTERISTICS;
 2.1 CONTACTRESISTANCE:40mΩ Max
 2.2 CONTACT CURRENT RATING:1A
 2.3 DIELECTRIC WITHSTANDING VOLTAGE:500 V

2.4 INSULATION RESISTANCE: 100 MEGOHMS Min
 2.5 OPERATING TEMPERATURE:-25°C ~ 85°C
 3 MECHANICAL CHARACTERISTICS:
 3.1 MATING FORCE:2Kgf Max
 3.2 UNMATED FORCE:INITIAL 0.4Kgf~2Kgf INITIAL;
 AFTER 30 CYCLES 0.15Kgf Min .
 3.3 DURABILITY:30 CYCLES
 4.⊗ MARK IS FAI DIM. ▲ MARK IS CPK DIM.

ITEM	PARTS	Q'TY	MATERIAL	REMARK
3	PEG	2	C2680	80u"Min Sn PLATING OVER ALL, 50u"Min Ni UNDER PLATING OVER ALL.
2	CONTACT	2	C2680	4u" AU ON THE CONTACT AREA, 2u" AU ON THE SOLDER AREA, 50u"Min Ni UNDER PLATING OVER ALL,
1	HOUSING	1	LCP	UL94V-0,BLACK

版次REV.		日期 DATE	变更内容 DESCRIPTION	审核 CHK.	核准 APPD.	单位 UNIT mm	一般公差 GENERAL TOLERANCE X.X ±0.25 X.XX ±0.10 X.XXX ±0.05	绘图 DR. Jimmy	WJCT 苏州伟聚电子科技有限公司	料号 PART NO. W-00-1209-0200
						▲ MAJOR DIM.	审核 CHK. Peak. ke	品名 TITLE 1. 2PH BTW CONN H1.45 RECEPTACLE 2P		图号 DRAWING NO. 500-0002-0006
1	2	3	4	5	6	7	8	核准 APPD. Rain. Pan	比例 SCALE 1/1	版次 REV. A